



Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers



### Specific benefits



#### Comfort

- 3D comfort foam integrated into harness that provides comfort and breathability for prolonged use
- Thermoformed belt provides lumbar support and optimal comfort



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Performance

- Certification above maximum rated load 100kg: product certified at 150kg



#### Ease of Use

- Ergonomic design facilitates user movement
- NFC system guarantees traceability

### Applications

- Public Works
- Finishing Works/Craftsmanship
- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Mining

### Certifications and norms



CE CATEGORY

**EN361**

150 KG

**EN813**

150 KG

**EN358**

### Risk Protection



Fall



Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

### Standards - Details

### Technical details

Type of equipment	Fall arrest, support and suspension harnesses
Composition of the main support	Aluminum, Polyester
Fastening	Buckles
Number of attachment points	2
Number of total suspension points	1
Number of total holding attachment points	2
Anti-fall point	Dorsal, Sternal
Suspension point	Ventral
Holding point	Belt
Color	Grey-Yellow
Comfort elements	"Soft padding" on shoulders and thigh strap, Thermocompressed back and shorts
Size	S/M/L, XL/XXL
Benefits element	Comfort, Fall indicator
Number of non-removable buckles	4
Weight (kg)	2,5
Number of manual buckles	2
Number of automatic loops	2
Number of fall arrest anchorage points	2
Padding	Back, Belt, Leg
Sternal	1
Dorsal	1
Use	120° rotation
Belt	1
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m),

	Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
--	---








Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

### Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
HAR35RPT	Grey-Yellow	SM	LYNX HAR35R	3295249270216	13295249270213	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HAR35RGT	Grey-Yellow	MD/LG	LYNX HAR35R	3295249265304	13295249265301	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HAR35RXX	Grey-Yellow	XL/2X	LYNX HAR35R	3295249265311	13295249265318	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height